

# SING EASY TL456

## PASSIVE COLUMN LOUDSPEAKER



The Sing Easy TL456 is specially developed for every kind of sound installation. With a very fashionable design, this range of loudspeakers fits with every architectural structure.

The Sing Easy TL456 is a cost-effective-high-quality column speaker, in a wooden cabinet and houses four 4.5-inch loudspeakers which generate a frequency bandwidth response of 150 Hz to 20 kHz.

These stylish 6-ohm loudspeakers with an incredibly dynamic and complete sound are well-suited for medium-sized mainly speech applications where the clear, uniformly dispersed sound that is audible at a distance is essential, such as conference centers, houses of worship or venues with highly reflective interior surfaces and at the same time, in combination with any Sing Easy subwoofer, an optimized music reproduction of the full range.

### MAIN APPLICATIONS

- Public address installation
- Place of worship
- Convention centres
- Hotels
- Outdoor music and speech use

### SPECIFICATIONS

Full-Range Frequency Driver	6 × 4.5-inch (114.3 mm)
Frequency Response (±3 dB)	150 Hz to 20 kHz
Sensitivity (1w@1m)	98 dB
Nominal Impedance	6 ohms
Power Ratings	Continuous 300 W Peak 1200 W
SPL Output	122 dB
Mounting Methods	Integral pole mount socket
Input Connectors	2 × NL4 connectors
Dimensions (H × W × D)	810 × 145 × 175 mm

