



Introducing the Sing Easy TRSAMPBT, the first-ever headphone amplifier wall plate designed to wirelessly transmit audio to any device supported by 5181 chipset, fully compliant with the latest 5.4 standard.

Experience top-notch, high-fidelity sound powered by advanced 5181 chipset. Perfect for both enthusiasts and professionals, TRSAMPBT boasts v5.4 and Class 1 connectivity, ensuring reliable performance over extended distances. Thanks to its built-in 4dB antenna, enjoy dependable reach beyond 10 meters.

With Smart Search capabilities, the device automatically enters pairing mode for 120 seconds after being powered on, making connectivity a breeze.

Supports a range of the industry's most advanced codecs:

- LDAC / Lossless (The Gold Standard)
- Adaptive HQ
- Adaptive LL
- HD / Low Latency
- AAC / SBC

Elevate your audio experience with the Sing Easy TRSAMPBT today!

FEATURES

- Audiophile Sound. Pro-Level Control
- Smart Search: Automatically enters pairing mode for 120 seconds upon power-on
- Supports cycle switching of up to 8 devices. When the 9th device is added, the earliest paired device will be automatically replaced
- Broadcast your audio to multiple devices simultaneously
- Built-in 4dB antenna for dependable reach over 10 meter
- Real-time Codec Status

SPECIFICATIONS

Power Input Connector	Phoenix connector 3.5mm 2-pin
Audio Input Connector	Phoenix connector 3.5mm 3-pin
Audio Input Level	<1Vrms
Frequency Response	20 Hz to 20 kHz
SNR	≥88dB
Distortion	≤ 0.1%
Sensitivity	-96 DBM @ 0.1% BER
Power Input	5V to 15V VDC
Power Consumption	12 mA
Form Factor	1 Gang US
Dimensions (H × W × D)	124mm × 79.5mm × 60mm (4.88in × 3.13 × 2.36in)
Weight	554 g (19.54 oz)
Warranty Period	36 months from date of purchase
US Tariff Code	8543.70.9860

The specifications are subject to be changed without notice.